

Larisplast LP 340

Meets the Israeli standards # 896

<p>High performance superplasticising admixture that addelerate the primary strength of the concrete. Produces workable, sealed and durable concrete. Without chlorides.</p>	<p><u>Dosage:</u> 0.4%-2.5% from the cement weight including PFA or microsilica. Possible to use different dosages for special works, but then it requires preliminary experience.</p>
<p><u>Description:</u> LP 340 is superplasticising admixture based on composite and improved Synthetic polymers materials.</p>	
<p><u>Advantages:</u> LP 340 improves the characters of fresh and hard concrete. Higher workability and easy to pour. Initial and final higher strength. Longer life and higher degree of sealing. Improved architectural concrete. Better concrete finishing.</p> <p><u>Durability and impermeability:</u> Based on the water/cement ratio, concrete becomes more dense, less porous, and harder to penetrate. Thus, there is less penetration of aggregates elements and the concrete becomes more durable.</p>	<p><u>Specific data:</u> Thin, brown color. SPECIFIC GRAVITY: 1.19 (± 0.05) at 20° C. PH: 8 (± 1).</p> <p><u>Instruction for use:</u> LP 340 add only after adding 50%-70% of water. Do not add the admixture to dry aggregates. Mix until the concrete is homogenous.</p> <p><u>Packaging:</u> In 1,000 liter containers.</p>
<p><u>Use:</u> Supplies high initial and final strength. Suitable especially for tropic weather. Improves workability of ready mix concrete and precast concrete. Improves durability and permeability of concrete.</p>	<p><u>Storage:</u> Length of storage not to exceed 12 months. Store in temperature of + 5° to + 40° C. The freezing point is approx -2° C.</p>

LarisPLAST Ltd.

ADVANCED PRODUCTS FOR CONCRETE AND BUILDING

Suitable:

For all type of work with cement.
For all type ordinary Portland cement and
with addition of PFA or microsilica.

Safety:

LP 340 is not defined as dangerous
material.
Avoid direct contact with skin and eyes.
Use gloves.
In case of contact with the material wash
immediately with plenty of water and seek
medical advice.
Not for eating.

Fire:

LP 340 is based on water and is not
flammable.

For additional information, please contact Larisplast.

13 Habonim st Kiriath Gat 8211202 ISRAEL
Tel:972-86204040 , Fax:972-8-6460321
E-mail:stella@larisplast.com
www.larisplast.com