

WATERPROOFING ADMIXTURE FOR CONCRETE AND MORTAR

DESCRIPTION

Conmix W1 is a permeability reducing admixture in liquid form for use in all types of mortar and concrete mixes.

Conmix W1 conforms to ASTM C494-81 Type A and BS 1881 : Part 5 1970.

USES & ADVANTAGES

Conmix W1 may be used to waterproof concrete structures such as: reservoirs, tunnels, culverts, water tanks, swimming pools and other areas where waterproof concrete or mortar is required.

Advantages include:-

- Improves workability and cohesion.
- Improves strength and durability.
- Reduces shrinkage.
- Reduces permeability.
- Chloride free.
- Allows better compaction.
- No effect on drinking water in concrete tanks.

PROPERTIES

Appearance : Brown liquid

Bulk Density : 1.15 - 1.18 kg/litre

APPLICATION

Conmix W1 should be dispensed with the mixing water.

Conmix W1 is compatible with most other admixtures, however, as **Conmix W1** has a water reducing effect and limited retardation trial mixes should be undertaken before pouring concrete. Overdosing will cause some retardation of initial set the concrete should not be disturbed but left to cure properly.

In case of overdose, extended retardation or mixing with other admixtures contained in the concrete consult Cormix International Technical Department.

CURING

Concrete containing **Conmix W1** still requires adequate curing use **Corcure 90**.

DOSAGES

0.2 - 0.5% by weight of cement. Trial mixes are always recommended before starting work to ascertain the best dosage level.

PACKAGING

25 Litre plastic pails and 200 litre steel drums.

STORAGE & SHELF LIFE

Conmix W1 should preferably be stored protected from frost. If the product does become frozen it should be carefully mixed after thawing out.

The shelf life is a minimum of 12 months in original unopened packaging.

HEALTH & SAFETY

Conmix W1 is formulated from chemicals which present no fire or health hazards.

For further information consult Cormix International.

TECHNICAL SERVICE

The Cormix International Technical Service Department is available to assist you in the correct use of our products and its resources are at your disposal entirely without obligation.

QUALITY ASSURANCE

Certified by



CONTACT DETAILS

Cormix International Limited

Regional Office,

15/1, Romklao Rd., Sansab, Minburi, Bangkok 10510

Tel. (66 2) 917 3955-8, 543 8890

Fax. (66 2) 917 3959, 543 8891

<http://www.cormix.com> E-mail : mkt@cormix.com

Rev. 008 : Jun 2005

NOTE : Every reasonable precaution is taken in the manufacture of all CORMIX-products to ensure that they comply with CORMIX's high standard of quality. The recommendations and properties of the product are based upon what is believed to be the most reliable information available, and are not intended as recommendations which infringe on other patents. Although all CORMIX-products are subject to rigid quality tests, no specific guarantee can be given, because results depend, not only on quality, but also on other factors beyond our control. We welcome therefore consultation in the event of doubt concerning application, or performance, and point out that oral recommendations, which vary from the instructions contained herein, are not binding without written confirmation by CORMIX. All transactions shall be subject to our terms and conditions of sale-delivery-and-service. This data sheet supersedes the previous one and a reprint may be issued without notice to supersede this edition, as and when deemed necessary. The information given in this leaflet is to the best of our knowledge true and reliable. Field service where provided does not constitute supervisory responsibility. Our guarantee is therefore limited to the quality of materials delivered.