



The oxy-acetylene fusion torch to preheat
and fuse Eutalloy® RW coatings

CastoFuse®



- Shut-off lever to interrupt quickly the oxygen and fuel gas supply. Adjustment of the valves not necessary for new operating procedure
- Powerful Monoblock valves enables higher flow rates and a more precise adjustment
- Simple to use through ergonomic design
- Higher operational safety through large cross-sectional area
- Complete kit-range of heating tips for every heating job





The advantage of local heating using CastoFuse® torch is obvious compared with an oven.

Local preheating and fusing prevents the dispersion of heat in the rest of the work piece, to the surrounding area and into the oven walls. CastoFuse® offers the heat where needed. Furthermore, only a small investment is required.

Designed for easy operation

More comfortable to use and, thereby, greater production can be achieved with this torch. The in-line control valves are positioned so that they can even be adjusted by operator whilst wearing gloves. The unique rapid shut-off lever allows the torch to be relit without touching any other control. All components are easily accessible for maintenance.

Safety features

Greater resistance to flashbacks because of the large cross-sectional area. This ensures that the required gas flow rate, even on heavy duty applications with low gas pressures, is still maintained. Certified to DQS level.




The CastoFuse® kit consists of a handgrip with three fusion lances 20, 30 and 40. The kit's three lances offer different flame powers, so work pieces of different mass or thickness can be preheated and heated up to the coating fusion temperature.

Tip CastoFuse	20	30	40
Oxygen consumption	0,75 - 1,1 m3/h	1,2 - 1,7 m3/h	2,3 - 3,3 m3/h
Acetylene consumption	0,7 - 1,0 m3/h	1,1 - 1,5 m3/h	2,1 - 3,0 m3/h
Flame power	~11,5 KW	~20 KW	~40 KW
Required 50l acetylene cylinder	1	2	4
Length	270 mm	320 mm	590 mm

CastoFuse KIT complete ESC: 290020 | item number: 71606580

Optional accessories

- Additional lance with high capacity
- For maximum safety, the pair of gas hoses with quick-fit connectors and antiflashback devices are recommended.



Your resource for protection, repair and joining solutions

Statement of Liability: Due to variations inherent in specific applications, the technical information contained herein, including any information as to suggest product applications or results, is presented without representation or warranty, expressed or implied. Without limitation, there are no warranties of merchantability or of fitness for a particular purpose. Each process and application must be fully evaluated by the user in all respects, including suitability, compliance with applicable law and non-infringement of the rights of others, and Messer Eutectic Castolin and its affiliates shall have no liability in respect thereof.